

PVC REINFORCED HOSE



APPLICATIONS

For Compressed air, water, gas, oil and many kinds of chemicals.

FEATURE

- Transparent visibility
- Light weight and flexible
- Standard pressure

MATERIAL

Clear PVC with braided

TEMPERATURE

-10°C to 60°C

Code	Nominal Size	I.D. (mm)	O.D. (mm)	Working / Burst Pressure (bar)	Weight (kg/m)	Length per roll (mt)
PA - 1006	1/4"	6.0	11.0	10 / 30	0.09	100
PA - 1008	5/16"	8.0	13.5	10 / 30	0.12	100
PA - 1009	3/8"	9.5	15.0	10 / 30	0.14	100
PA - 1012	1/2"	12.5	18.0	8 / 24	0.17	100
PA - 1015	5/8"	16.0	22.0	8 / 24	0.24	50
PA - 1019	3/4"	19.0	26.0	6 / 18	0.33	50
PA - 1025	1"	25.0	32.0	6 / 18	0.42	50
PA - 1032	1 1/4"	32.0	41.0	5 / 15	0.69	40
PA - 1038	1 1/2"	38.0	48.0	5 / 15	0.91	40
PA - 1050	2"	50.0	62.0	5 / 15	1.42	40