

## BUNKERING HOSE 10 BAR

*(Complies to RMA Grade RM)*



### Common Applications

Hardwall hose used for the suction and discharge of petroleum products from tankers and barges, bunkering service and industrial applications; suitable for aromatic content up to 50%. Available with swaged-on fittings or built-in fittings.

### Tube

Black, smooth, synthetic rubber, suitable for aromatic content up to 50%.

### Reinforcement

High strength synthetic cord, steel helix wire and anti-static copper wire.

### Cover

Black, smooth (wrapped finish), synthetic rubber resistant to weather, oil and sea water.

### Temperature Range

- 20°C to + 82°C

### Electrical characteristics

Electrically continuous.

### Safety Factor

4 : 1

Product Code	Nominal inch	I.D. mm	O.D. mm	Working/Burst Pressure Bar	Weight Kg/Mt	Volume M <sup>3</sup>	Coil Length Mt
RPS 3075	3	76.2	94.0	10 / 40	3.65	0.530	30 / 60
RPS 3100	4	101.6	124.0	10 / 40	5.99	1.116	30 / 60
RPS 3150	6	152.4	182.0	10 / 40	11.84	2.764	30 / 40
RPD 3200	8	203.2	235.0	10 / 40	17.08	5.948	30 / 40

• Other sizes, colours and lengths available on request.